

**OVERLAPPED AND SHADOWED TREE CROWN SEGMENTATION  
BASED ON HSI COLOR MODEL AND WATERSHED ALGORITHM**

**SENOSY SULIMAN MOHAMED ARRISH**

**UNIVERSITI TEKNOLOGI MALAYSIA**

OVERLAPPED AND SHADOWED TREE CROWN SEGMENTATION BASED  
ON HSI COLOR MODEL AND WATERSHED ALGORITHM

SENOSY SULIMAN MOHAMED ARRISH

A dissertation submitted in partial fulfillment of the  
requirement for the award of the degree of  
Master of Science (Computer Science)

Faculty of Computing  
Universiti Teknologi Malaysia

JANUARY 2014

Dedicated, in thankful appreciation for support, encouragement and understanding to  
my beloved mother, my beloved father "Allah mercy", my beloved brothers and  
*sisters, and beloved friend.*

## ACKNOWLEDGEMENT

First of all, all praise is due to ALLAH Almighty for His compassion and mercifulness to allow me finalizing this Master thesis. Special thanks to my parents, father and mother, who take care of me since I was born until this moment where they did not stop praying for me, day and night, for help and success in this life. My thanks go to all my family members who support and help me along the course of this dissertation by giving encouragement and providing moral and emotional support I need to complete my thesis. To them, I am deeply grateful.

I would like to thank my supervisor, Prof.Dr. Dzulkifli Mohamad, who guided me in selecting the final theme for this research. My supervisor was there throughout my preparation of the proposal and the conceptualization of its structure. Without his help and support, I would not have been able to do the research and achieve learning in the same manner. His recommendations and instructions have enabled me to assemble and finish the dissertation effectively.

I would also like to thank UTM for supporting and encouraging student to give their best. Additional deep thanks to all my instructors and lecturers, who throughout my educational career have supported and encouraged me to believe in my abilities. This research will not be completed without the contributions of Libyan National Oil Corporation (NOC) for giving me scholarship and supporting this research by offering to pay the fees of the data that has been used in this research. I highly appreciate this help. Last but not least, I appreciate the help and support from all persons who directly or indirectly involved in my project and I don't want to forget to thank my best friends Ahmed Sany who were helping and supporting my effort.

## **ABSTRACT**

Image provides valuable information to the human and this information could be used to take an effective dissection such as information that comes from satellite sensors. Satellite images let the human have the information from the ground for very wide area. The negative side of satellite image is the resolution is still not much high. Satellite image play a vital role in many area of our live, especially agriculture, where the human can calculate the crown of the tree for very wide area in very short time. The counting of tree will not be accurate without getting good segmentation of these crowns. This work has applied segmentation algorithm to separate crown of coconut palm tree from shadow and the overlapped crown as well. The algorithm has exploited HSI color model to differentiate the color of crown from the color of shadow. The result of using this feature gives very different color for both shadow and crown. After crown detection the algorithm used morphological operation such as image filling to enhance the crown. The following step is removing noise or pixels which considered unwanted objects. Finally, the image was segmented using watershed after applying distance transform on the image. Since this research does not has ground information to measure the accuracy, the evaluation has been done manually, where the crown has counted manually and calculate the accuracy of this work which is 73%.

## ABSTRAK

Sesuatu imej berkeupayaan memberikan informasi berharga kepada manusia dan informasi ini dapat digunakan untuk mendapatkan perincian yang efektif sebagai contoh informasi yang berasal dari sensor satelit. Imej satelit membolehkan manusia mendapatkan informasi dari permukaan tanah yang sangat luas. Tetapi dari sudut negatifnya, tahap resolusi imej tersebut masih tidak tinggi. Imej satelit memainkan peranan penting dalam pelbagai bidang hidup manusia terutamanya pertanian, yang mana manusia dapat menghitung silara pokok untuk sesuatu kawasan yang sangat luas dalam waktu yang sangat singkat. Penghitungan pokok tidak akan mendapat nilai yang tepat tanpa melakukan segmentasi yang baik dari silara pokok tersebut. Kajian ini telah menerapkan algoritma segmentasi untuk memisahkan silara pokok kelapa sawit dari bayang-bayangnya dan juga silara pokok yang bertindih. Algoritma telah mengeksploitasi model warna HSI untuk membezakan warna silara pokok dari warna bayang-bayangnya. Hasil dari penggunaan ciri ini telah memberikan warna yang sangat berbeza untuk bayang-bayang dan silara pokok. Setelah pengesanan silara pokok, operasi morfologi iaitu Image Filling digunakan untuk meningkatkan imej silara pokok. Langkah berikutnya adalah menyingkirkan noise atau piksel yang dianggap sebagai objek yang tidak diinginkan dan diakhiri dengan segmentasi imej dengan menggunakan teknik Watershed setelah mengubah imej dengan menggunakan teknik Distance Transform. Oleh kerana ketiadaan data pokok dari tanah untuk mengukur ketepatan kajian ini, penilaian telah dilakukan secara manual yang mana silara pokok telah dikira secara manual dan ketepatan kajian ini telah mencapai nilai sehingga 73%.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	<b>DECLARATION</b>	<b>ii</b>
	<b>DEDICATION</b>	<b>iii</b>
	<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
	<b>ABSTRACT</b>	<b>vi</b>
	<b>ABSTRAK</b>	<b>vii</b>
	<b>TABLE OF CONTENTS</b>	<b>viii</b>
	<b>LIST OF TABLES</b>	<b>xi</b>
	<b>LIST OF FIGURES</b>	<b>xii</b>
	<b>LIST OF APPENDICES</b>	<b>xiv</b>
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Introduction	1
	1.2 Research Background	2
	1.3 Problem Statement	5
	1.4 Research Aim	6
	1.5 Research Objective	6
	1.6 Research Scope	6
	1.7 Research Significance	7
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>8</b>
	2.1 Introduction	8
	2.2 Remote Sensing	9

2.2.1	Quality Type of Remote Sensing Data	9
2.2.2	Satellite Sensors	11
2.3	Problem that Face Delineation Algorithm for Tree Crown	12
2.3.1	Congestion “Overlap” of the Crowns	12
2.3.2	Shadow of the Palm Crown	13
2.3.3	The Cloud in the Satellite Image	14
2.3.4	Detecting Palm Tree among Other Kind of Tree	15
2.3.5	The Background	16
2.3.6	Altitude and the Contrast of the Crown in the Image	18
2.3.7	The Topology Variation of the Forest Area	19
2.3.8	The Various Ages of the Palm Tree	19
2.4	Previous Work	20
2.4.1	K-Mean Segmentation Algorithms	20
2.4.2	Watershed Segmentation Algorithms	24
2.4.3	Region Growing Algorithms	27
2.4.4	Valley –Following Algorithms	32
2.5	Summary Previous Work	32
2.6	Conclusion	40
<b>3</b>	<b>RESEARCH METHODOLOGY</b>	<b>41</b>
3.1	Introduction	41
3.2	Dataset	42
3.3	Used Hardware and Software	43
3.4	Proposed Method	44
3.5	Read Image	47
3.6	Pre-Processing	47
3.6.1	Convert RGB Colour Space to HSI Colour Space	47
3.6.2	Increase the Value of Saturation	48
3.7	Detect the Crown Using Colour Information	49
3.8	Crown Enhancement	49
3.8.1	Convert Image to Grey, then to Black and White	50



3.8.2	Image Erode	50
3.8.3	Image Filling	51
3.8.4	Image Dilate	52
3.9	Unwanted Blob Removal	52
3.9.1	Remove Connected Pixels Less than 50	53
3.9.2	Remove Pixels Bigger than 2500	53
3.10	Crown Segmentation	53
3.10.1	Mapping Image Using Distance Transform	54
3.10.2	Apply Watershed for DT Matrix	54
3.11	Accuracy Measurement	57
<b>4</b>	<b>RESULTS AND DISSCUSION</b>	<b>58</b>
4.1	Introduction	58
4.2	The Result of Each Stage in the Algorithm	59
4.3	Benchmarking	65
<b>5</b>	<b>CONCLUSION</b>	<b>70</b>
5.1	Introduction	70
5.2	Contributions	71
5.3	Future Works	71
5.4	Conclusion	72
	<b>REFERENCES</b>	<b>73</b>
	<b>APPENDICES A</b>	<b>77</b>
	<b>APPENDICES B</b>	<b>82</b>

**LIST OF TABLES**

<b>TABLE NO</b>	<b>TITLE</b>	<b>PAGE</b>
2.1	Some Sensor types and their resolution	11
3.1	Specification of used hardware and software	43
4.1	The result of Watershed from different experiment	65
4.2	Accuracy measurement on crowns without shadow separation	66
4.3	Accuracy Measurements after shadow separation	66
4.4	Benchmarking the result of crown segmented with shadow against crown segmented without shadow	67

## LIST OF FIGURES

FIGURE NO	TITLE	PAGE
1.1	Two crown shapes; (a) for palm tree; (b) for other type of trees	3
2.1	Spatial Resolution	10
2.2	Wavelength range	10
2.3	Figure show the congestion of the Palm tree	13
2.4	The crown of the palm and its shadow have the same shape	14
2.5	The clouds hide the details of the vegetation region	15
2.6	Many types of trees growing in the same field	16
2.7	Color similarity between crown and the background	17
2.8	Palm tree in non-green background	17
2.9	One region from different altitudes	18
2.10	The neighbors with distance $d=1$ , $d=2$	22
2.11	Palm tree among other kind of trees	23
2.12	How the watershed works, the grey pixels are the highest value comparing to the 8 connected neighbors, and the white pixels are the lowest value	24
2.13	Figure shows the isolation process	26
2.14	The algorithm introduced in (Kubo et al., 2007)	27
2.15	The Region Growing Algorithms	28
2.16	The algorithm steps in (Zhao et al., 2008)	30
2.17	Vegetation object after merging	31
2.18	Crown object after merging	31
2.19	Crown mode segmentation	32

3.1	Area of research data	42
3.2	Testing Area	43
3.3	Proposed Algorithm framework	46
3.4	Structure element used for erode image	51
3.5	Image filling example	51
3.6	Structure element 5*5 used for dilation image	52
3.7	Sample of applying distance transform	54
3.8	Watershed algorithm component	55
3.9	Image A is binary image, B is the image after distance transform mapping and C is the image after applying watershed algorithm	55
3.10	The relationship between $X_h$ and $Y_{h+1}$	56
4.1	Reading original image with shadow and overlapped crown	59
4.2	Convert image to HSI colour space	60
4.3	Crown detection	60
4.4	Shadow detection	61
4.5	Convert crown image to grey colour	61
4.6	Convert grey image to black and white	62
4.7	Image erosion	62
4.8	Image filling	63
4.9	Image dilation	63
4.10	Remove unwanted objects	63
4.11	Mapping image using distance transform	64
4.12	Applying watershed algorithm	64
4.13	Marking crown using “+” sign	64
4.14	The accuracy measurement on the image 3 with and without shadow separation	68
4.15	The accuracy measurement on the image 6 with and without shadow separation	69

**LIST OF APPENDICES**

<b>FIGURE NO</b>	<b>TITLE</b>	<b>PAGE</b>
A	Data specification that have been used in this research	77
B	The satellite's sensor types and features	81

## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Introduction**

Tree plantation is one of the significant resources for supporting the economy of every country. Nowadays, different types of trees are used for producing different things around us such as chemical, fuel, food, cosmetic products. Due to the huge demand on tree-based products, the number of planted trees is expected to rise, especially after discovering that tree products could replace fossil fuel as the latter is expected as well to end. The key advantage for biofuel is being a clean energy that does not affect and pollute the air as it is with fossil fuel which emits Carbon in the air.

Therefore, as trees are valuable, there have been problems of managing the vast amount of trees in forests and counting them on hundreds of hectares. Counting trees would be cumbersome to laborers when they have to work on very wide areas. Such manual counting is time consuming, error-prone, and costing money.

The issue we are going to address now is how to employ technologies to do the task of identifying and counting palm trees, where there is an urgent need to find

a method that can delineate and count them. This kind of information should be accurate because it will be used for counting the costs and revenues.

In brief, tree delineation and counting techniques are new research areas and till now they face many problems which will be elaborated later. Manual tree counting is an expensive way to do the plantation inventory in forest areas. The technology should introduce some solutions to solve counting tree from satellite image instead of doing it manually on the ground.


## **1.2 Research Background**

There have been many researches made on identifying the crown of a tree, but those made on the area of palm tree detection are few such as (Shafri *et al.*, 2011; Jusoff and Pathan, 2009; Arasato *et al.*, 2011). The available research on palm tree counting is not sufficient and did not satisfy the need for counting enormous palm trees on wide area with high accuracy. Furthermore, most papers did not focus on advanced issues in palm tree segmentation such as overlapping, shadow and shape complex.

Shafri *et al.* (2011) is the most recent research on palm tree where it mentioned that very few papers have discussed the problem of counting palm tree. The paper gave good results, however there are some vital problems which their proposed approach could not solve such as crown overlapping even though it has considered in palm tree younger than the age of 10 where the crown is very small. The other thing which should not be omitted is that their algorithm could not distinguish the shape of the palm tree and the other kinds of tree, where the shape of palm tree have a unique shape which look like a star comparing to be like other kind of trees that does not have such unique shape.

The objective in (Arasato *et al.*, 2011) were to identify palm trees over other objects/trees using videography collected using an air craft mission over the Amazon. Region growing was used as the segmenting algorithm while two classification methods were used, i.e. K-mean and visual analysis (negative contrast/positive contrast). The segmentation process was depending on real color composition (positive contrast), but colors cannot be used for classification every time as some trees could have or carry the same level of colors and lighting can affect the color level.

There is lack of research on the palm tree delineation and counting, meanwhile there are plenty of papers on tree counting as general. The difference between palm trees and normal trees is the shape of the crown. The crown of Normal trees takes irregular shapes and sometimes round-like shapes. On the other hand palm trees take distinct star-like shapes as shown in figure 1.1.



**Figure 1.1** Two crown shapes; (a) for palm tree; (b) for other type of trees

There are some of algorithms that have been implemented to segment and count trees; the following algorithms are popular in this field of research: The Valley Following Approach, Region Growing, Watershed Algorithm, Template Matching, and Marked Point Model Algorithm.



The Valley Following algorithm was developed by Gougeon where the concept of this approach considers crowns as mountains and the background as valley as in (Ke and Quackenbush, 2011; Leckie *et al.*, 2005) who employed this method. The shortcoming in this algorithm is that it cannot segment overlapped crowns and separate crowns and their shadows.

The Watershed Algorithm is a popular algorithm that has been used widely for segmenting trees, however, this method have not been used to segment palm trees according to our best knowledge. The concept of watershed is to find the area between the crown, where this algorithm deals with local maxima as local minima and vice versa. Many papers used this algorithm such as (Kwak *et al.*, 2007; Silván-Cárdenas, 2012; Kubo *et al.*, 2007) to segment and isolate crowns from the background and to avoid the over-segmentation effect. Another algorithm based on the watershed algorithm is the Marker-Controlled Watershed which was developed by Meyer and Beucher in 1990 (Ke and Quackenbush, 2011). The backward in this algorithm is that being working on greyscale image, therefore, it will not be able to differentiate a crown and its shadow.

The K-mean is used for clustering and segmenting crowns where the concept of this approach is to segment or cluster the image into k number of segments where each one is made based on the centroid point for each cluster. It was used for isolating trees in (Moreno-Garcia *et al.*, 2010) where K-crowns were isolated. K-mean algorithm is not an appropriate algorithm to solve advanced problems such as overlapped crowns and shadows due to ignoring color levels in the image.

The Region Growing Algorithm is a common algorithm which segments crowns and objects. The core principle in Region growing approach is to get the starting point or seed point and a segmentation process grows based on the neighboring pixels similar to the seed. The process will stop when some conditions become true. There are many works that used this approach such as (Arasato *et al.*, 2011; Deng *et al.*, 2010; Deng *et al.*, 2011).

This algorithm has a limitation for not distinguishing crowns and their shadows and also not overcoming overlapped crowns as it works with greyscale images, thus ignoring color levels.

The Template Matching is another approach that has not been used for crown segmentation. The idea of this approach does not rely completely on clear visible trees. Instead, it relies on matching with other images or templates; when there is a similarity between an image and the template, a matching case is announced as in (Erikson, 2004). This algorithm costs a lot because it needs some information from the ground to be matched with the sensed one.

Overall, there are few researches which work on palm tree counting and segmenting. Palm tree counting is a very new topic as all these research are recent. The tree crown detection is different from palm tree in terms of the crown's shape.

### **1.3 Problem Statement**

The agriculture industry needs reliable information to control, monitor and manage forest, but the issue is that the manual or the conventional estimation of the palm tree counting cost too much in terms of time, money and labor force. Therefore there is a need for an automated or semi-automated method that can count palm trees. And in order to do so, a system needs to segment and delineate palm trees' crown first, as system cannot work without this step which is the core issue in many researches. The accuracy of counting trees relies on the method that has been used to isolate the crown and the area in the testing image. There are many problems that occur when identifying palm trees from satellite image but the most critical problems that we focus on in this research are crowns' shadows segmentation and overlapped crown segmentation. We believed that these two problems were not widely discussed in the literature reviewed in chapter 2. Thus, they are addressed here to further the research related to them.

## **1.4 Research Aim**

This dissertation aims to find an automated method to segment and separate the crown of a palm tree to be used later for estimating or counting how many crowns in satellite image.

## **1.5 Research Objective**

1. To develop a method for segmenting palm tree from satellite image using color information and the Watershed Algorithm.
2. To evaluate the accuracy of the proposed techniques.

## **1.6 Research Scope**

- The data is satellite image with 3 bands, i.e. Red, Green and Blue.
- This research will focus on palm tree, where the palm tree grow up in many types of areas such as forest area and desert area, the data that have been used in this research have non-green background.
- The palm trees in the dataset have overlapping crowns.
- The size of the image will be varying, because it is not an issue and it can be determined automatically.
- Area testing field has the size of 25.
- Resolution of this data is 0.5 per pixel

## **1.7 Research Significance**

This research is very important for monitoring and estimating the number of palm trees on the ground. This kind of research will enhance and boost the agriculture industry because it gives information on the number of trees. Stakeholders can then estimate the amount of water that will be consumed, fertilizers, and man power to do certain tasks such as harvesting.

## REFERENCES

- Arasato, L. S., Amaral, S., Rennó, C. D., Epiphanyo, J. C. N. and Galvão, L. S. 2011. Detecting Individual Palm Trees (Arecaceae Family) in the Amazon Rainforest Using High Resolution Image Classification. *Simpósio Brasileiro de Sensoriamento Remoto, 15 (SBSR)*. 7628-7635.
- Ardila, J. P., Tolpekin, V. A., Bijker, W. and Stein, A. 2011. Markov-Random-Field-Based Super-Resolution Mapping for Identification of Urban Trees in Vhr Images. *ISPRS Journal of Photogrammetry and Remote Sensing*. 66(6), 762-775.
- Bazi, Y., Al-Sharari, H. and Melgani, F. 2009. An Automatic Method for Counting Olive Trees in Very High Spatial Remote Sensing Images. *Proceedings of the 2009 IEEE Geoscience and Remote Sensing Symposium, 2009 IEEE International, IGARSS 2009*. IEEE, II-125-II-128.
- Deng, G., Li, Z. and Wu, H. 2010. Tree Crown Recognition Algorithm on High Spatial Resolution Remote Sensing Imagery. *Proceedings of the 2010 IEEE Image and Signal Processing (CISP), 2010 3rd International Congress on*. IEEE, 2278-2281.
- Deng, G., Li, Z., Wu, H. and Zhang, X. 2011. Automated Extracting Tree Crown from Quickbird Stand Image. *Computer and Computing Technologies in Agriculture Iv*. (pp. 304-311) Springer.
- Erikson, M. 2004. Species Classification of Individually Segmented Tree Crowns in High-Resolution Aerial Images Using Radiometric and Morphologic Image Measures. *Remote Sensing of Environment*. 91(3-4), 469-477.
- Erikson, M. and Olofsson, K. 2005. Comparison of Three Individual Tree Crown Detection Methods. *Machine Vision and Applications*. 16(4), 258-265.
- Gonzalez, J., Galindo, C., Arevalo, V. and Ambrosio, G. 2007. Applying Image Analysis and Probabilistic Techniques for Counting Olive Trees in High-

- Resolution Satellite Images. *Proceedings of the 2007 Springer Advanced Concepts for Intelligent Vision Systems*. Springer, 920-931.
- Hart, N. and Huang, L. 2012. Counting Insects in Flight Using Image Processing Techniques. *Proceedings of the 2012 ACM Proceedings of the 27th Conference on Image and Vision Computing New Zealand*. ACM, 274-278.
- Jusoff, K. and Pathan, M. 2009. Mapping of Individual Oil Palm Trees Using Airborne Hyperspectral Sensing: An Overview. *Applied Physics Research*. 1(1), P15.
- Ke, Y. and Quackenbush, L. J. 2011. A Comparison of Three Methods for Automatic Tree Crown Detection and Delineation from High Spatial Resolution Imagery. *International Journal of Remote Sensing*. 32(13), 3625-3647.
- Koch, B., Heyder, U. and Weinacker, H. 2006. Detection of Individual Tree Crowns in Airborne Lidar Data. *Photogrammetric Engineering and Remote Sensing*. 72(4), 357.
- Komura, R. and Muramoto, K.-i. 2007. Classification of Forest Stand Considering Shapes and Sizes of Tree Crown Calculated from High Spatial Resolution Satellite Image. *Proceedings of the 2007 IEEE Geoscience and Remote Sensing Symposium, 2007. IGARSS 2007. IEEE International*. IEEE, 4356-4359.
- Kubo, M., Nishikawa, S., Yamamoto, E. and Muramoto, K.-i. 2007. Identification of Individual Tree Crowns from Satellite Image and Image-to-Map Rectification. *Proceedings of the 2007 IEEE Geoscience and Remote Sensing Symposium, 2007. IGARSS 2007. IEEE International*. IEEE, 1905-1908.
- Kwak, D.-A., Lee, W.-K., Lee, J.-H., Biging, G. S. and Gong, P. 2007. Detection of Individual Trees and Estimation of Tree Height Using Lidar Data. *Journal of Forest Research*. 12(6), 425-434.
- Larsen, M., Eriksson, M., Descombes, X., Perrin, G., Brandtberg, T. and Gougeon, F. A. 2011. Comparison of Six Individual Tree Crown Detection Algorithms Evaluated under Varying Forest Conditions. *International Journal of Remote Sensing*. 32(20), 5827-5852.
- Leckie, D. G., Gougeon, F. A., Tinis, S., Nelson, T., Burnett, C. N. and Paradine, D. 2005. Automated Tree Recognition in Old Growth Conifer Stands with High Resolution Digital Imagery. *Remote Sensing of Environment*. 94(3), 311-326.
- Moreno-Garcia, J., Linares, L. J., Rodriguez-Benitez, L. and Solana-Cipres, C. 2010.

- Olive Trees Detection in Very High Resolution Images. *Information Processing and Management of Uncertainty in Knowledge-Based Systems. Applications.* (pp. 21-29) Springer.
- Niccolai, A. M., Hohl, A., Niccolai, M. and Dearing Oliver, C. 2010. Decision Rule-Based Approach to Automatic Tree Crown Detection and Size Classification. *International Journal of Remote Sensing.* 31(12), 3089-3123.
- Pitkänen, J., Maltamo, M., Hyypä, J. and Yu, X. 2004. Adaptive Methods for Individual Tree Detection on Airborne Laser Based Canopy Height Model. *International Archives of Photogrammetry, Remote Sensing and Spatial Information Sciences.* 36(8), 187-191.
- Pouliot, D., King, D., Bell, F. and Pitt, D. 2002. Automated Tree Crown Detection and Delineation in High-Resolution Digital Camera Imagery of Coniferous Forest Regeneration. *Remote Sensing of Environment.* 82(2), 322-334.
- Rafael C. Gonzalez, R. E. W. 2002. *Digital Image Processing 2 Edition.* Tom Robbins.
- Shafri, H. Z., Hamdan, N. and Saripan, M. I. 2011. Semi-Automatic Detection and Counting of Oil Palm Trees from High Spatial Resolution Airborne Imagery. *International Journal of Remote Sensing.* 32(8), 2095-2115.
- Silván-Cárdenas, J. L. 2012. A Segmentation Method for Tree Crown Detection and Modelling from Lidar Measurements. *Pattern Recognition.* (pp. 65-74) Springer.
- Song, C., Dickinson, M. B., Su, L., Zhang, S. and Yaussey, D. 2010. Estimating Average Tree Crown Size Using Spatial Information from Ikonos and Quickbird Images: Across-Sensor and across-Site Comparisons. *Remote Sensing of Environment.* 114(5), 1099-1107.
- Tatiraju, S. and Mehta, A. 2008. Image Segmentation Using K-Means Clustering, Em and Normalized Cuts. *University Of California Irvine.*
- Trichon, V. 2001. Crown Typology and the Identification of Rain Forest Trees on Large-Scale Aerial Photographs. *Plant Ecology.* 153(1-2), 301-312.
- Vibha, L., Shenoy, P., Venugopal, K. and Patnaik, L. 2009. Robust Technique for Segmentation and Counting of Trees from Remotely Sensed Data. *Proceedings of the 2009 IEEE Advance Computing Conference, 2009. IACC 2009. IEEE International.* IEEE, 1437-1442.

- Zhao, F., Zhang, H., Li, Z. and Pang, Y. 2008. The Extraction of Individual Tree-Crown in Aerial Digital Camera Imagery. *Proceedings of the 2008 IEEE Fuzzy Systems and Knowledge Discovery, 2008. FSKD'08. Fifth International Conference on.* IEEE, 183-188.
- Zhou, J., Proisy, C., Couteron, P., Descombes, X., Zerubia, J., le Maire, G. and Nouvellon, Y. 2011. Tree Crown Detection in High Resolution Optical Images During the Early Growth Stages of Eucalyptus Plantations in Brazil. *Proceedings of the 2011 IEEE Pattern Recognition (ACPR), 2011 First Asian Conference on.* IEEE, 623-627.
- Zhou, J., Proisy, C., Descombes, X., Hedhli, I., Barbier, N., Zerubia, J., Gastellu-Etchegorry, J.-P. and Couteron, P. 2010. Tree Crown Detection in High Resolution Optical and Lidar Images of Tropical Forest. *Proceedings of the 2010 International Society for Optics and Photonics Remote Sensing.* International Society for Optics and Photonics, 78240Q-78240Q-6.